

Diametri Diameters	Limiti Limits	H	M	S	E	P
M 4	Min.	4,70	2,90	6,78	7,66	~ 0,70
	Max	5,00	-	7,00	-	
M 5	Min.	4,70	3,20	7,78	8,79	~ 0,80
	Max	5,00	-	8,00	-	
M 6	Min.	5,70	4,00	9,78	11,05	~ 1,00
	Max	6,00	-	10,00	-	
M 8	Min.	7,64	5,50	12,73	14,38	~ 1,25
	Max	8,00	-	13,00	-	
M 10	Min.	9,64	6,50	16,73	18,90	~ 1,50
	Max	10,00	-	17,00	-	
M 12	Min.	11,57	8,00	18,67	21,10	~ 1,75
	Max	12,00	-	19,00	-	

- Acciaio a media resistenza
- Classe 6S
- Carico di durezza:
- Materiale inserto:

89 HRB Min
polyamide

- Medium tensile steel
- Class 6S steel
- Hardness load minimum:
- Insert material:

89 HRB Min
polyamide

Dadi utilizzati in svariati settori industriali, meccanici ed artigianali in abbinamento a bulloni, viti e/o rondelle. L'inserto in nylon consente una maggiore resistenza allo svitamento.

Nuts used in various industrial, mechanical and craftwork sectors in conjunction with bolts, screws and/or washers. The nylon bit offers a major resistance to loosening.


FINITURA / FINISHING

**MISURE
SIZES
Ø**




Zincate
CR3
Blue zinc
CR3

IMBALLO / PACKAGING


MISURE SIZES Ø	FINITURA / FINISHING	IMBALLO / PACKAGING	IMBALLO / PACKAGING	IMBALLO / PACKAGING
M 4	14,65	24000 (24)	4000 (4)	1000
M 5	16,95	12000 (24)	2000 (4)	500
M 6	22,00	6000 (12)	2000 (4)	500
M 8	47,70	4000 (8)	2000 (4)	500
M 10	94,65	1600 (8)	800 (4)	200
M 12	136,90	1200 (6)	400 (2)	200

Prezzi per 1.000 pz - Euro prices/1.000 pcs



Diametri Diameters	Limiti Limits	H	M	S	E	P
M 5	Min.	6,00	4,40	7,78	8,79	~ 0,80
	Max	6,30	-	8,00	-	
M 6	Min.	7,00	4,90	9,78	11,05	~ 1,00
	Max	8,00	-	10,00	-	
M 8	Min.	9,14	6,44	12,73	14,38	~ 1,25
	Max	9,50	-	13,00	-	
M 10	Min.	11,14	8,04	16,73	18,90	~ 1,50
	Max	11,50	-	17,00	-	
M 12	Min.	13,64	10,37	18,67	21,10	~ 1,75
	Max	14,00	-	19,00	-	

- Acciaio a media resistenza
- Classe 6S
- Carico di durezza:
- Materiale inserto:

89 HRB Min
polyamide

- Medium tensile steel
- Class 6S steel
- Hardness load minimum:
- Insert material:

89 HRB Min
polyamide

Dadi utilizzati in svariati settori industriali, meccanici ed artigianali in abbinamento a bulloni, viti e/o rondelle. L'inserto in nylon consente una maggiore resistenza allo svitamento.

Nuts used in various industrial, mechanical and craftwork sectors in conjunction with bolts, screws and/or washers. The nylon bit offers a major resistance to loosening.


FINITURA / FINISHING

**MISURE
SIZES
Ø**



Zincate
CR3
Blue zinc
CR3

IMBALLO / PACKAGING


MISURE SIZES Ø	FINITURA / FINISHING	IMBALLO / PACKAGING	IMBALLO / PACKAGING	IMBALLO / PACKAGING
M 5	18,55	12000 (24)	2000 (4)	500
M 6	28,05	6000 (12)	2000 (4)	500
M 8	56,80	3000 (6)	1000 (2)	500
M 10	118,10	1200 (6)	400 (2)	200
M 12	168,50	800 (4)	400 (2)	200

Prezzi per 1.000 pz - Euro prices/1.000 pcs