


- Acciaio
- Classe 100 HV

- Steel
- Class 100 HV steel

Diametri Diameters	Limiti Limits	D1	D2	S
M 3	Min.	3,20	6,64	0,45
	Max	3,38	7,00	0,55
M 4	Min.	4,30	8,64	0,70
	Max	4,48	9,00	0,90
M 5	Min.	5,30	9,64	0,90
	Max	5,48	10,00	1,10
M 6	Min.	6,40	11,57	1,40
	Max	6,62	12,00	1,80
M 8	Min.	8,40	15,57	1,40
	Max	8,62	16,00	1,80
M 10	Min.	10,50	19,48	1,80
	Max	10,77	20,00	2,20
M 12	Min.	13,00	23,48	2,30
	Max	13,27	24,00	2,70
M 14	Min.	15,00	27,48	2,30
	Max	15,27	28,00	2,70
M 16	Min.	17,00	29,48	2,70
	Max	17,27	30,00	3,30
M 18	Min.	19,00	33,38	2,70
	Max	19,33	34,00	3,30
M 20	Min.	21,00	36,38	2,70
	Max	21,33	37,00	3,30
M 22	Min.	23,00	38,38	2,70
	Max	23,33	39,00	3,30
M 24	Min.	25,00	43,38	3,70
	Max	25,33	44,00	4,30
M 27	Min.	28,00	49,38	3,70
	Max	28,33	50,00	4,30
M 30	Min.	31,00	55,26	3,70
	Max	31,39	56,00	4,30







Rondelle utilizzate in svariati settori industriali, meccanici ed artigianali in abbinamento a bulloni, viti e/o dadi.

Washers used in various industrial, mechanical and craftwork sectors in conjunction with bolts, screws and/or nuts.



"sempre al tuo fianco nel mondo del fissaggio"

FINITURA / FINISHING		IMBALLO / PACKAGING		
MISURE SIZES Ø				
	Zincate CR3 Blue zinc CR3			
M 3	4,25	48000 (24)	8000 (4)	2000
M 4	5,50	48000 (24)	8000 (4)	2000
M 5	6,50	24000 (12)	8000 (4)	2000
M 6	10,20	24000 (12)	8000 (4)	2000
M 8	17,40	12000 (12)	4000 (4)	1000
M 10	30,00	6000 (6)	2000 (2)	1000
M 12	48,00	4000 (4)	2000 (2)	1000
M 14	65,00	2000 (4)	1000 (2)	500
M 16	83,30	2000 (4)	1000 (2)	500
M 18	113,70	800 (4)	400 (2)	200
M 20	121,90	800 (4)	400 (2)	200
M 22	150,00	400 (4)	200 (2)	100
M 24	248,00	400 (4)	200 (2)	100
M 27	318,80	400 (4)	200 (2)	100
M 30	487,00	400 (4)	200 (2)	100